



Palomino™
INDUSTRIAL BATTERY CHARGERS

03/28/11

The Power of Excellence

PRODUCT: Multi-Shift Battery Charger

APPLICATION: 80% depleted full recharge in 8 hours or less.

SPECIFICATIONS & PRICE LIST **Three (3) Phase**

Model	Cell (voltage)	Battery Amp Hour Range	Phase	DC Output Current	Input Current	Output Cable ga. AWG	Weight Lbs. (kg.)
208 VOLTS*							
12 B 0540 B HB	12 (24V)	475-540	3	87	9	1/0	176 (80)
12 B 0600 B HB	12 (24V)	541-600	3	96	11	1/0	188 (85)
12 B 0750 B HB	12 (24V)	600-750	3	120	13	1/0	199 (90)
12 B 0875 B HB	12 (24V)	751-875	3	140	15	1/0	212 (96)
12 B 1050 B HB	12 (24V)	876-1050	3	168	18	1/0	225 (102)
18 B 0540 B HB	18 (36V)	476-540	3	87	13	1/0	208 (94)
18 B 0600 B HB	18 (36V)	541-600	3	96	15	1/0	217 (98)
18 B 0750 B HB	18 (36V)	600-750	3	120	18	1/0	226 (102)
18 B 0875 B HB	18 (36V)	751-875	3	140	21	1/0	257 (116)
18 B 0965 B HB	18 (36V)	876-965	3	154	24	1/0	267 (121)
18 B 1050 B HB	18 (36V)	966-1050	3	168	25	1/0	277 (125)
18 B 1260 B HB	18 (36V)	1051-1260	3	202	31	2/0	295 (133)
24 B 0475 B HB	24 (48V)	380-475	3	76	15	2	226 (102)
24 B 0600 B HB	24 (48V)	475-600	3	96	19	1/0	244 (110)
24 B 0750 B HB	24 (48V)	600-750	3	120	24	1/0	277 (125)
24 B 0875 B HB	24 (48V)	751-865	3	140	28	1/0	310 (140)
24 B 1050 B HB	24 (48V)	966-1050	3	168	33	1/0	326 (148)
240 VOLTS*							
12 B 0540 B JC	12 (24V)	475-540	3	87	8	1/0	176 (80)
12 B 0600 B JC	12 (24V)	541-600	3	96	10	1/0	188 (85)
12 B 0750 B JC	12 (24V)	600-750	3	120	11	1/0	199 (90)
12 B 0875 B JC	12 (24V)	751-875	3	140	13	1/0	212 (96)
12 B 1050 B JC	12 (24V)	876-1050	3	168	15	1/0	225 (102)
18 B 0540 B JC	18 (36V)	476-540	3	87	11	1/0	208 (94)
18 B 0600 B JC	18 (36V)	541-600	3	96	13	1/0	217 (98)
18 B 0750 B JC	18 (36V)	600-750	3	120	15	1/0	226 (102)
18 B 0875 B JC	18 (36V)	751-875	3	140	18	1/0	257 (116)
18 B 0965 B JC	18 (36V)	876-965	3	154	20	1/0	267 (121)
18 B 1050 B JC	18 (36V)	966-1050	3	168	22	1/0	277 (125)
18 B 1260 B JC	18 (36V)	1051-1260	3	202	27	2/0	295 (133)
24 B 0475 B JC	24 (48V)	380-475	3	76	13	2	226 (102)
24 B 0600 B JC	24 (48V)	475-600	3	96	16	1/0	244 (110)
24 B 0750 B JC	24 (48V)	600-750	3	120	21	1/0	277 (125)
24 B 0875 B JC	24 (48V)	751-865	3	140	24	1/0	310 (140)
24 B 1050 B JC	24 (48V)	966-1050	3	168	29	1/0	326 (148)

Palomino (3ph) - Specifications & Price List Continued

Model	Cell (voltage)	Battery Amp Hour Range	Phase	DC Output Current	Input Current	Output Cable ga. AWG	Weight Lbs. (kg.)
480 VOLTS*							
12 B 0540 B KD	12 (24V)	475-540	3	87	4	1/0	176 (80)
12 B 0600 B KD	12 (24V)	541-600	3	96	5	1/0	188 (85)
12 B 0750 B KD	12 (24V)	600-750	3	120	5	1/0	199 (90)
12 B 0875 B KD	12 (24V)	751-875	3	140	6	1/0	212 (96)
12 B 1050 B KD	12 (24V)	876-1050	3	168	8	1/0	225 (102)
18 B 0540 B KD	18 (36V)	476-540	3	87	6	1/0	208 (94)
18 B 0600 B KD	18 (36V)	541-600	3	96	7	1/0	217 (98)
18 B 0750 B KD	18 (36V)	600-750	3	120	8	1/0	226 (102)
18 B 0875 B KD	18 (36V)	751-875	3	140	9	1/0	257 (116)
18 B 0965 B KD	18 (36V)	876-965	3	154	10	1/0	267 (121)
18 B 1050 B KD	18 (36V)	966-1050	3	168	11	1/0	277 (125)
18 B 1260 B KD	18 (36V)	1051-1260	3	202	13	2/0	295 (133)
24 B 0475 B KD	24 (48V)	380-475	3	76	6	2	226 (102)
24 B 0600 B KD	24 (48V)	475-600	3	96	8	1/0	244 (110)
24 B 0750 B KD	24 (48V)	600-750	3	120	10	1/0	277 (125)
24 B 0875 B KD	24 (48V)	751-865	3	140	12	1/0	310 (140)
24 B 1050 B KD	24 (48V)	966-1050	3	168	14	1/0	326 (148)

Freight allowed

***These units are single AC input voltages; they can't be changed to alternate voltages.**

- > Supplied with a 10 ft. DC output cable and output connector.
- > Dimensions: B Cabinet = 22" width X 22" depth X 26" height
- > Please refer to Warranty Certificates for warranty information.
- > UL listed for U.S. and Canadian safety standards.