



COLT SCR
INDUSTRIAL BATTERY CHARGERS

06/02/08

The Power of Excellence

PRODUCT: Colt - SCR Cell charger

APPLICATION: Battery charger with selectable profiles that mounts in the battery tray.

MODEL: **A15125**

Cell rating: **12 cell (24V)**

Case style: **Large case = 12.25" W x 4.94" H x 18.12" L**

SPECIFICATIONS & PRICE LIST

Profile Suffix #	Amp Hour Rating	High Rate Current	Gassing Voltage (vpc)	Finish Rate Current	Finish Rate Timer (Hrs)
GEL 1 PROFILE					
D2	225	16	2.33	-	6
D3	380	20	2.33	-	6
D5	510	32	2.33	-	6
GEL 2 PROFILE					
E2	260	20	2.40	4	6
E3	380	25	2.40	6	6
E5	510	40	2.40	8	6
AGM PROFILE					
G2	260	25	2.35	7	3
G3	380	25	2.35	11	3
G5	510	40	2.35	15	3
FLOODED PROFILE					
F2	260	20	2.37 or 2.45	11	3
F3	380	25	2.37 or 2.45	16	3
F5	510	40	2.37 or 2.45	22	3

How to order:
Factory set profile =
Model # + profile suffix #
(ex. A15125F3 = 380ah flooded profile)

Shipping terms for 10pcs or more:

F.O.B. Caledonia, NY, price includes freight to first U.S. destination (excluding AK & HI). Please consult Applied Energy Solutions for any additional requirements.

Similar Products

Application	Product
Light duty, single shift with 10 to 16 hrs for charging	WorkHorse Series 1

- > Supplied with AC line cord.
- > Please refer to Warranty Certificates for warranty information.
- > UL Listed & UL Listed to Canadian Safety Standard
- > Applied Energy Solutions is an ISO 9001 Registered U.S. Manufacturer.