



**MAVERICK™ MultiPro™ OPPORTUNITY CHARGER**

03/28/11

*The Power of Excellence*

**PRODUCT:** Maverick MultiPro High Frequency Opportunity Charger

**APPLICATION:** Opportunity charging without battery modifications and automatic voltage detection.



**SPECIFICATIONS & PRICE LIST Three (3) Phase**

Model	Cell (voltage)	AH	Phase	DC Output Current	Amp Draw @ 480 Volts AC	Output Cable ga. AWG	Charger Weight Lbs. (kg.)	Weight (w/packing material) Lbs. (kg.)
HFM 012 T 1000 J MD	12 (24V)	380-1000	3	95-250	3.9-11.4	2/0	126 (57)	147 (67)
HFM 018 T 1000 J MD	18 (36V)	380-1000	3	95-250	5.2-13.8	2/0	129 (59)	150 (69)
HFM 024 T 0865 J MD	24 (48V)	380-865	3	95-216	6.7-15.6	2/0	129 (59)	150 (69)

**FREIGHT ADDER**

*\*\*Units must all be shipping to the same address \*\**

**1-4 Units \$80.00 per unit**  
**5+ Units Freight paid by AES**

- > Supplied 10 ft. DC output cable and output connector.
- > Dimensions: J Cabinet = 22" width X 22" depth X 19" height
- > Please refer to Warranty Certificates for warranty information.
- > UL Listed & UL Listed to Canadian Safety Standard