



STABLEMATE CONSTANT CURRENT INDUSTRIAL BATTERY CHARGERS

06/02/08

The Power of Excellence

PRODUCT: StableMate - Constant current chargers

APPLICATION: Shop, rental, or loaner charger that charges any battery in the cell range.

➔ SPECIFICATIONS & PRICE LIST

Model	Cabinet Style	DC Output Current	Cell (voltage) Range	Phase	Input Current / Voltage	AC line cord and plug type	Weight Lbs. (kg.)
StableMate 25							
A15237	Standard	25	1 to 24 (2V-48V)	1	16A @ 120 VAC	NEMA 5-20P	75 (34)
A15236NW	Heavy Duty w/o handle & wheels	25	1 to 24 (2V-48V)	1	16A @ 120 VAC	NEMA 5-20P	170 (77)
A15236	Heavy Duty w/handle & wheels	25	1 to 24 (2V-48V)	1	16A @ 120 VAC	NEMA 5-20P	175 (79)
StableMate 50							
A15238NW	Heavy Duty w/o handle & wheels	50	1 to 24 (2V-48V)	1	16A @ 240 VAC	NEMA 6-20P	185 (84)
A15238	Heavy Duty w/handle & wheels	50	1 to 24 (2V-48V)	1	16A @ 240 VAC	NEMA 6-20P	190 (86)
StableMate 50HV							
A15561-B	Heavy Duty	50	18 to 40 (36V-80V)	1	30A @ 208 VAC	NA	225 (102)
A15561-C	Heavy Duty	50	18 to 40 (36V-80V)	1	26A @ 240 VAC	NA	225 (102)
A15561-D	Heavy Duty	50	18 to 40 (36V-80V)	1	13A @ 480 VAC	NA	225 (102)

Shipping: F.O.B. Caledonia, NY, price includes freight to first U.S. destination (excluding AK & HI). Please consult Applied Energy Solutions for any additional requirements.

➔ Similar Products

Application	Product
1 charger to charge multiple batteries with different cell and amp hour ratings.	Maverick MultiPro High Frequency Charger

- > Supplied with an 8 ft. DC output cable with dual output connectors (SB175 & SB350) in a steel enclosure.
- > Dimensions: Standard Duty Cabinet = 15.5" width X 13" depth X 16.5" height
 Heavy Duty Cabinet = 23" width X 17.5" depth X 22.2" height
 Heavy Duty w/handles & wheels Cabinet = 23" width X 17.5" depth X 32" height
- > Please refer to Warranty Certificates for warranty information.
- > UL listed for U.S. & Canadian safety standards.
- > Applied Energy Solutions is an ISO 9001 Registered U.S. Manufacturer.