



WARHORSE MULTI-CIRCUIT INDUSTRIAL BATTERY CHARGERS

The Power of Ex

PRODUCT: WarHorse - Multicircuit -Three Shift Battery Charger

APPLICATION: Save space, charge multiple batteries, 100% depleted battery fully recharged in 8 hours or

➔
SPECIFICATIONS & PRICE LIST
Three (3) P

Model	Cell (voltage)	Circuits	Battery Amp Hour Range	Phase	DC Output Current per circuit	Input Current:				Output Cable (ga. AWG)	Weight Lbs. (kg.)
						B 208 VAC Input Voltage	C 240 VAC Input Voltage	D 480 VAC Input Voltage	E 575 VAC Input Voltage		
12 R 0600 Z 3 * 2 T	12 (24V)	2	541-600	3	105	24	22	10	-	1/0	461
12 R 0600 Z 9 * 2 T	12 (24V)	2	541-600	3	105	-	22	10	8	1/0	461
12 R 0680 Z 3 * 2 T	12 (24V)	2	601-680	3	131	28	24	12	-	1/0	486
12 R 0680 Z 9 * 2 T	12 (24V)	2	601-680	3	131	-	24	12	10	1/0	486
12 R 0750 Z 3 * 2 T	12 (24V)	2	681-750	3	131	28	24	12	-	1/0	486
12 R 0750 Z 9 * 2 T	12 (24V)	2	681-750	3	131	-	24	12	10	1/0	486
12 R 0865 Z 3 * 2 T	12 (24V)	2	751-865	3	151	32	28	14	-	1/0	502
12 R 0865 Z 9 * 2 T	12 (24V)	2	751-865	3	151	-	28	14	12	1/0	502
12 R 0965 Z 3 * 2 T	12 (24V)	2	866-965	3	169	38	32	16	-	1/0	590
12 R 0965 Z 9 * 2 T	12 (24V)	2	866-965	3	169	-	32	16	14	1/0	590
12 R 1050 Z 3 * 2 T	12 (24V)	2	966-1050	3	184	42	36	18	-	1/0	590
12 R 1050 Z 9 * 2 T	12 (24V)	2	966-1050	3	184	-	36	18	16	1/0	590
12 R 1200 Z 3 * 2 T	12 (24V)	2	1051-1200	3	210	46	40	20	-	2/0	610
12 R 1200 Z 9 * 2 T	12 (24V)	2	1051-1200	3	210	-	40	20	16	2/0	610
12 R 1450 Z 3 * 2 T	12 (24V)	2	1201-1450	3	254	54	46	24	-	2/0	610
12 R 1450 Z 9 * 2 T	12 (24V)	2	1201-1450	3	254	-	46	24	20	2/0	610
18 R 0600 Z 3 * 2 T	18 (36V)	2	541-600	3	105	36	32	16	-	1/0	546
18 R 0600 Z 9 * 2 T	18 (36V)	2	541-600	3	105	-	32	16	12	1/0	546
18 R 0680 Z 3 * 2 T	18 (36V)	2	601-680	3	131	42	36	18	-	1/0	561
18 R 0680 Z 9 * 2 T	18 (36V)	2	601-680	3	131	-	36	18	12	1/0	561
18 R 0750 Z 3 * 2 T	18 (36V)	2	681-750	3	131	42	36	18	-	1/0	561
18 R 0750 Z 9 * 2 T	18 (36V)	2	681-750	3	131	-	36	18	12	1/0	561
18 R 0865 Z 3 * 2 T	18 (36V)	2	751-865	3	151	50	44	22	-	1/0	578
18 R 0865 Z 9 * 2 T	18 (36V)	2	751-865	3	151	-	44	22	18	1/0	578
18 R 0965 Z 3 * 2 T	18 (36V)	2	866-965	3	169	54	48	24	-	1/0	630
18 R 0965 Z 9 * 2 T	18 (36V)	2	866-965	3	169	-	48	24	20	1/0	630
18 R 1050 Z 3 * 2 T	18 (36V)	2	966-1050	3	184	60	50	26	-	1/0	630
18 R 1050 Z 9 * 2 T	18 (36V)	2	966-1050	3	184	-	50	26	22	1/0	630
18 R 1200 Z 3 * 2 T	18 (36V)	2	1051-1200	3	210	68	58	32	-	2/0	745
18 R 1200 Z 9 * 2 T	18 (36V)	2	1051-1200	3	210	-	58	32	26	2/0	745

WarHorse - Multicircuit (3 ph) - Specifications & Price List Continued

Model	Cell (voltage)	Circuits	Battery Amp Hour Range	Phase	DC Output Current per circuit	Input Current:				Output Cable (ga. AWG)	Weight Lbs. (kg.)
						B 208 VAC Input Voltage	C 240 VAC Input Voltage	D 480 VAC Input Voltage	E 575 VAC Input Voltage		
18 R 1450 Z 3 * 2 T	18 (36V)	2	1201-1450	3	254	78	68	34	-	2/0	745
18 R 1450 Z 9 * 2 T	18 (36V)	2	1201-1450	3	254	-	68	34	30	2/0	745
24 R 0600 Z 3 * 2 T	24 (48V)	2	541-600	3	105	48	42	20	-	1/0	541
24 R 0600 Z 9 * 2 T	24 (48V)	2	541-600	3	105	-	42	20	16	1/0	541
24 R 0750 Z 3 * 2 T	24 (48V)	2	681-750	3	131	56	48	24	-	1/0	592
24 R 0750 Z 9 * 2 T	24 (48V)	2	681-750	3	131	-	48	24	20	1/0	592
24 R 0865 Z 3 * 2 T	24 (48V)	2	751-865	3	151	66	58	28	-	1/0	675
24 R 0865 Z 9 * 2 T	24 (48V)	2	751-865	3	151	-	58	28	24	1/0	675
24 R 0965 Z 3 * 2 T	24 (48V)	2	866-965	3	169	72	64	32	-	1/0	730
24 R 0965 Z 9 * 2 T	24 (48V)	2	866-965	3	169	-	64	32	26	1/0	730
24 R 1050 Z 3 * 2 T	24 (48V)	2	966-1050	3	184	80	70	34	-	1/0	732
24 R 1050 Z 9 * 2 T	24 (48V)	2	966-1050	3	184	-	70	34	28	1/0	732
24 R 1200 Z 3 * 2 T	24 (48V)	2	1051-1200	3	210	92	78	40	-	2/0	769
24 R 1200 Z 9 * 2 T	24 (48V)	2	1051-1200	3	210	-	78	40	30	2/0	769
36 R 0260 Z 3 * 2 T	36 (62v)	2	181-260	3	46	28	24	12	-	2	481
36 R 0380 Z 3 * 2 T	36 (62v)	2	261-380	3	67	46	40	20	-	2	600
36 R 0475 Z 3 * 2 T	36 (62v)	2	381-475	3	83	56	48	24	-	2	600
36 R 0600 Z 3 * 2 T	36 (62v)	2	541-600	3	105	72	62	32	-	1/0	729
36 R 0750 Z 3 * 2 T	36 (62v)	2	681-750	3	131	82	72	36	-	1/0	729
36 R 0865 Z 3 * 2 T	36 (62v)	2	751-865	3	151	100	86	44	-	1/0	745
36 R 0965 Z 3 * 2 T	36 (62v)	2	866-965	3	169	110	94	48	-	1/0	760
40 R 0180 Z 3 * 2 T	40 (80)	2	120-180	3	32	20	18	8	-	2	490
40 R 0475 Z 3 * 2 T	40 (80)	2	381-475	3	86	54	48	24	-	2	675
40 R 0475 Z 9 * 2 T	40 (80)	2	381-475	3	86	-	48	24	20	2	675
40 R 0540 Z 3 * 2 T	40 (80)	2	476-540	3	97	62	54	26	-	1/0	695
40 R 0540 Z 9 * 2 T	40 (80)	2	476-540	3	97	-	54	26	22	1/0	695
40 R 0600 Z 3 * 2 T	40 (80)	2	541-600	3	108	68	58	30	-	1/0	695
40 R 0600 Z 9 * 2 T	40 (80)	2	541-600	3	108	-	58	30	26	1/0	695
40 R 0750 Z 3 * 2 T	40 (80)	2	681-750	3	135	86	74	38	-	1/0	765
40 R 0750 Z 9 * 2 T	40 (80)	2	681-750	3	135	-	74	38	32	1/0	765

Shipping: F.O.B. Caledonia, NY, price includes freight to first U.S. destination (excluding AK & HI). Please consult Applied Energy Solutions for any additional requirements.

* = indicates incoming VAC: (B=208, C=240, D=480, E=575)

WarHorse - Multicircuit (3 ph) - Specifications & Price List Continued

 **Similar Products**

Application	Product
Cold storage or sealed batteries - heavy duty, three shift operation.	Steed
Opportunity charging	QuarterHorse
1 charger to charge multiple batteries with different cell and amp hour ratings	Maverick MultiPro High Freq

- > Supplied with a 10 ft. DC output cable and output connector.
- > Dimensions: **Z** Cabinet = 30" width X 28" depth X 37" height
- > Please refer to Warranty Certificates for warranty information.
- > UL listed for U.S. and Canadian safety standards.
- > Applied Energy Solutions is an ISO 9001 Registered U.S. Manufacturer.


06/02/08

cellence

less.

'hase

mysol.com



Agency Charger

