



MAVERICK™ HIGH FREQUENCY CEC CONVENTIONAL CHARGER

03/13/15

The Power of Excellence

→ SPECIFICATIONS & PRICE LIST

Three (3) Phase 480 Volt Only

Model	Cell Count	AH	Start Rate (%)	Start Rate (A)	Input Current (A) @ 480V
HFC 012 G 0540 L MD	12	540	18	97	3.97
HFC 012 G 0600 L MD	12	600	18	108	4.41
HFC 012 G 0680 L MD	12	680	18	122	4.97
HFC 012 G 0750 L MD	12	750	18	135	5.50
HFC 012 G 0865 L MD	12	865	18	156	6.34
HFC 012 G 1000 L MD	12	1000	18	180	7.31
HFC 018 G 0750 L MD	18	750	18	135	8.22
HFC 018 G 0865 L MD	18	865	18	156	9.49
HFC 018 G 1000 L MD	18	1000	18	180	10.94
HFC 024 G 0600 L MD	24	600	18	108	8.76
HFC 024 G 0680 L MD	24	680	18	122	9.89
HFC 024 G 0750 L MD	24	750	18	135	10.94
HFC 024 G 0865 L MD	24	865	18	156	12.63
HFC 024 G 1000 L MD	24	1000	18	180	13.70
HFC 024 G 1190 L MD	24	1190	18	214	15.90

→ Similar Products

Application	Product
Conventional charging	Workhorse 1, 2, & 3
Conventional charging	Steed
Conventional charging	Palomino
Conventional charging	Warhorse
Conventional / Opportunity charging	Maverick Opportunity, MultiPro
Conventional / Opportunity charging	Advanced Quarterhorse
Conventional charging	Stablemate

- > Supplied 10 ft. DC output cable and output connector.
- > Dimensions: L Cabinet = 22" width X 22" depth X 16" height
- > Please refer to Warranty Certificates for warranty information.
- > UL / CUL Listed