



MAVERICK™ HIGH FREQUENCY CONVENTIONAL

01/01/14

The Power of Excellence

SPECIFICATIONS & PRICE LIST

Three (3) Phase 480 Volt Only

Model	Cell Count	AH	Start Rate (%)	Start Rate (A)	Input Current (A) @ 480V
HFC 012 F 0380 L MD	12	380	18	68	2.80
HFC 012 F 0475 L MD	12	475	18	85	3.48
HFC 012 F 0540 L MD	12	540	18	97	3.97
HFC 012 F 0600 L MD	12	600	18	108	4.41
HFC 012 F 0680 L MD	12	680	18	122	4.97
HFC 012 F 0750 L MD	12	750	18	135	5.50
HFC 012 F 0865 L MD	12	865	18	156	6.34
HFC 012 F 1000 L MD	12	1000	18	180	7.31
HFC 012 F 1190 L MD	12	1190	18	214	9.40
HFC 012 F 1360 L MD	12	1360	18	244	11.40
HFC 018 F 0380 L MD	18	380	18	68	4.17
HFC 018 F 0475 L MD	18	475	18	85	5.19
HFC 018 F 0540 L MD	18	540	18	97	5.92
HFC 018 F 0600 L MD	18	600	18	108	6.59
HFC 018 F 0680 L MD	18	680	18	122	7.43
HFC 018 F 0750 L MD	18	750	18	135	8.22
HFC 018 F 0865 L MD	18	865	18	156	9.49
HFC 018 F 1000 L MD	18	1000	18	180	10.94
HFC 018 F 1190 L MD	18	1190	18	214	12.50
HFC 018 F 1360 L MD	18	1360	18	244	14.00
HFC 024 F 0380 L MD	24	380	18	68	5.54
HFC 024 F 0475 L MD	24	475	18	85	6.91
HFC 024 F 0540 L MD	24	540	18	97	7.88
HFC 024 F 0600 L MD	24	600	18	108	8.76
HFC 024 F 0680 L MD	24	680	18	122	9.89
HFC 024 F 0750 L MD	24	750	18	135	10.94
HFC 024 F 0865 L MD	24	865	18	156	12.63
HFC 024 F 1000 L MD	24	1000	18	180	13.70
HFC 024 F 1190 L MD	24	1190	18	214	15.90

Similar Products

Application	Product
Conventional charging	Workhorse 1, 2, & 3
Conventional charging	Steed
Conventional charging	Palomino
Conventional charging	Warhorse
Conventional / Opportunity charging	Maverick Opportunity, MultiPro
Conventional / Opportunity charging	Advanced Quarterhorse
Conventional charging	Stablemate

- > Supplied 10 ft. DC output cable and output connector.
- > Dimensions: L Cabinet = 22" width X 22" depth X 16" height
- > Please refer to Warranty Certificates for warranty information.
- > UL / CUL Listed