



MAVERICK™ HIGH FREQUENCY OPPORTUNITY CHARGER

01/21/14

The Power of Excellence

PRODUCT: Maverick High Frequency Opportunity Charger

APPLICATION: Opportunity charging without battery modifications.

➔ SPECIFICATIONS & PRICE LIST

Three (3) Phase

Model	Cell (voltage)	AH	Phase	DC Output Current	Amp Draw @ 480 Volts AC	Output Cable ga. AWG	Charger Weight Lbs. (kg.)	Weight (w/packing material) Lbs. (kg.)
HFC 012 C 0380 P MD	12 (24V)	380	3	95	3.9	1/0	121 (55)	142 (65)
HFC 012 C 0475 P MD	12 (24V)	475	3	118	4.9	1/0	121 (55)	142 (65)
HFC 012 C 0540 P MD	12 (24V)	540	3	135	5.6	1/0	121 (55)	142 (65)
HFC 012 C 0600 P MD	12 (24V)	600	3	150	6.2	1/0	121 (55)	142 (65)
HFC 012 C 0680 P MD	12 (24V)	680	3	170	7.1	1/0	121 (55)	142 (65)
HFC 012 C 0750 P MD	12 (24V)	750	3	187	7.8	1/0	121 (55)	142 (65)
HFC 012 C 0865 P MD	12 (24V)	865	3	216	9.4	2/0	123 (56)	144 (66)
HFC 012 C 0935 P MD	12 (24V)	935	3	230	10.8	2/0	126 (57)	147 (67)
HFC 012 C 1000 P MD	12 (24V)	1000	3	250	11.4	2/0	126 (57)	147 (67)
HFC 012 C 1100 P MD	12 (24V)	1100	3	275	12.6	4/0	126 (57)	147 (67)
HFC 012 C 1190 P MD	12 (24V)	1190	3	298	13.6	4/0	126 (57)	147 (67)
HFC 012 C 1360 P MD	12 (24V)	1360	3	340	15.6	4/0	126 (57)	147 (67)
HFC 018 C 0380 P MD	18 (36V)	380	3	95	5.2	1/0	121 (55)	142 (65)
HFC 018 C 0475 P MD	18 (36V)	475	3	118	6.4	1/0	121 (55)	142 (65)
HFC 018 C 0540 P MD	18 (36V)	540	3	135	7.3	1/0	121 (55)	142 (65)
HFC 018 C 0600 P MD	18 (36V)	600	3	150	8.1	1/0	124 (56)	145 (66)
HFC 018 C 0680 P MD	18 (36V)	680	3	170	9.2	1/0	124 (56)	145 (66)
HFC 018 C 0750 P MD	18 (36V)	750	3	187	10.1	1/0	124 (56)	145 (66)
HFC 018 C 0865 P MD	18 (36V)	865	3	216	12.1	2/0	129 (59)	150 (69)
HFC 018 C 0935 P MD	18 (36V)	935	3	230	13.0	2/0	129 (59)	150 (69)
HFC 018 C 1000 P MD	18 (36V)	1000	3	250	13.8	2/0	129 (59)	150 (69)
HFC 018 C 1100 P MD	18 (36V)	1100	3	275	15.4	4/0	129 (59)	150 (69)
HFC 018 C 1190 P MD	18 (36V)	1190	3	298	16.5	4/0	129 (59)	150 (69)
HFC 018 C 1360 P MD	18 (36V)	1360	3	340	19.0	4/0	129 (59)	150 (60)
HFC 024 C 0380 P MD	24 (48V)	380	3	95	6.7	1/0	121 (55)	142 (65)
HFC 024 C 0475 P MD	24 (48V)	475	3	118	8.3	1/0	121 (55)	142 (65)
HFC 024 C 0540 P MD	24 (48V)	540	3	135	9.4	1/0	121 (55)	142 (65)
HFC 024 C 0600 P MD	24 (48V)	600	3	150	10.4	1/0	127 (58)	148 (68)
HFC 024 C 0680 P MD	24 (48V)	680	3	170	11.9	1/0	127 (58)	148 (68)
HFC 024 C 0750 P MD	24 (48V)	750	3	187	13.3	1/0	127 (58)	148 (68)
HFC 024 C 0865 P MD	24 (48V)	865	3	216	15.6	2/0	129 (59)	150 (69)
HFC 024 C 0935 P MD	24 (48V)	935	3	230	16.9	2/0	129 (59)	150 (69)
HFC 024 C 1000 P MD	24 (48V)	1000	3	250	18.1	2/0	129 (59)	150 (69)
HFC 024 C 1100 P MD	24 (48V)	1100	3	275	20.0	4/0	129 (59)	150 (60)
HFC 024 C 1190 P MD	24 (48V)	1190	3	298	21.5	4/0	129 (59)	150 (69)

➔ Similar Products

Application	Product
Opportunity charging	Maverick Multipro
Opportunity charging	Advanced Quarterhorse

- > Supplied 10 ft. DC output cable and output connector.
- > Dimensions: P Cabinet = 22" width X 22" depth X 19" height
- > Please refer to Warranty Certificates for warranty information.
- > UL / CUL Listed